

**B**

**STEEL** THREADED RODS

Right-hand Threads  
THREADED FULL LENGTH

**Inch Sizes**

Grade: C1010 (or better)  
ASTM spec A-307  
Minimum tensile strength  
50,000 to 60,000 psi

The versatile do-it-yourself rod for making U-bolts, eye-bolts, hangers, ladder rungs, and many types of special items. Cold-drawn steel bends easily without heating. Just cut to desired length and use.



**Finishes: Plain and Zinc Plated**

*All Threaded Rods shown below are priced singly.*

**ORDER BY SPAENAUER NUMBERS LISTED BELOW**

THREAD SIZE	Plain		Zinc Pltd.		Plain		Zinc Pltd.		Plain		Zinc Pltd.	
	24" Lgth.	24" Lgth.	36" Lgth.	36" Lgth.	72" Lgth.	72" Lgth.	120" Lgth.	120" Lgth.	144" Lgth.	144" Lgth.	144" Lgth.	144" Lgth.
4-40	TR-44		866-055	866-055ZP								
5-40			866-012	866-012ZP								
6-32	TR-46	TR-46ZP	866-056	866-056ZP								
8-32	TR-48	TR-48ZP	866-057	866-057ZP								
10-24	TR-50	TR-50ZP	866-058	866-058ZP								
10-32	TR-52	TR-52ZP	866-059	866-059ZP								
12-24	TR-54	TR-54ZP	866-060	866-060ZP								
1/4"-20	866-146	866-146ZP	TR-4	TR-4ZP	866-013	866-013ZP	866-061	866-061ZP	866-130	866-130ZP		
1/4"-28	866-145	866-145ZP	866-001	866-001ZP								
5/16"-18	866-142	866-142ZP	TR-5	TR-5ZP	866-014	866-014ZP	866-062	866-062ZP	866-131	866-131ZP		
5/16"-24			866-002	866-002ZP								
3/8"-16			TR-6	TR-6ZP	866-015	866-015ZP	866-063	866-063ZP	866-079	866-079ZP		
3/8"-24			866-003	866-003ZP					866-054			
7/16"-14	866-143	866-143ZP	TR-7	TR-7ZP	866-016	866-016ZP	866-064	866-064ZP	866-132	866-132ZP		
7/16"-20			866-004	866-004ZP								
1/2"-13			TR-8	TR-8ZP	866-017	866-017ZP	866-065	866-065ZP	866-081	866-081ZP		
1/2"-20			866-005	866-005ZP								
9/16"-12			866-125	866-125ZP	866-127	866-127ZP	866-128	866-128ZP	866-129	866-129ZP		
9/16"-18			866-126	866-126ZP								
5/8"-11			TR-10	TR-10ZP	866-018	866-018ZP	866-066	866-066ZP	866-082	866-082ZP		
5/8"-18			866-006	866-006ZP								
3/4"-10			TR-12	TR-12ZP	866-019	866-019ZP	866-067	866-067ZP	866-083	866-083ZP		
3/4"-16			866-007	866-007ZP								
7/8"-9	866-144	866-144ZP	TR-14	TR-14ZP	866-020	866-020ZP	866-068	866-068ZP	866-084	866-084ZP		
7/8"-14			866-008	866-008ZP								
1"-8			TR-16	TR-16ZP	866-021	866-021ZP	866-124	866-124ZP	866-069	866-069ZP		
1"-14			866-009	866-009ZP								
1-1/8"-7			TR-18	TR-18ZP					866-070	866-070ZP		
1-1/8"-12			866-010	866-010ZP								
1-1/4"-7			TR-20	TR-20ZP					866-071	866-071ZP		
1-1/4"-12			866-011	866-011ZP								
1-3/8"-6			TR-22	TR-22ZP					866-072	866-072ZP		
1-3/8"-12			866-120	866-120ZP								
1-1/2"-6			TR-24	TR-24ZP					866-073	866-073ZP		
1-1/2"-12			866-121	866-121ZP								
1-5/8"-5-1/2			TR-26	TR-26ZP								
1-3/4"-5			TR-28	TR-28ZP					866-075	866-075ZP		
2"-4-1/2			TR-32	TR-32ZP					866-076	866-076ZP		

**Weight Chart for Steel Threaded Rod**  
Approximate Weight in Lbs. per Foot

Thread Size	Weight per Foot
4-40	.024 lbs.
5-40	.032 lbs.
6-32	.036 lbs.
8-32	.054 lbs.
10-24	.070 lbs.
12-24	.100 lbs.
1/4"-20	.120 lbs.
5/16"-18	.200 lbs.

Thread Size	Weight per Foot
3/8"-16	.290 lbs.
7/16"-14	.400 lbs.
1/2"-13	.540 lbs.
9/16"-12	.667 lbs.
5/8"-11	.834 lbs.
3/4"-10	1.240 lbs.
7/8"-9	1.667 lbs.
1"-8	2.223 lbs.

Thread Size	Weight per Foot
1-1/8"-7	2.667 lbs.
1-1/4" 7	3.334 lbs.
1-3/8"-6	4.112 lbs.
1-1/2"-6	4.667 lbs.
1-5/8"-5-1/2	6.334 lbs.
1-3/4"-5	7.000 lbs.
2"-4-1/2	9.112 lbs.

CATALOG 13