

STEEL



Assembled "K-LOK" Locknuts



Inch Sizes

STEEL, Zinc Plated

PRE-ASSEMBLED NUTS AND EXTERNAL LOCKWASHERS.
LOCKWASHERS FREE TO TURN BUT CANNOT DROP OFF.

UNC and UNF Threads


SPAENAUR No.	THREAD SIZE	WIDTH ACROSS FLATS	OVERALL THICKNESS	O.D. OF LOCKWASHER	SERIES	UNIT PKG. 100
N-180K	4-40	1/4"	1/8"	17/64"	AMERICAN STANDARD HEXAGON MACHINE SCREW NUT SERIES	
N-206K	5-40	5/16"	9/64"	11/32"		
N-1K	6-32	5/16"	9/64"	11/32"		
N-2K	8-32	11/32"	5/32"	3/8"		
N-3K	10-24	3/8"	5/32"	13/32"		
N-4K	10-32					
N-295K	12-24	7/16"	7/32"	1/2"	▲AMERICAN STANDARD HEXAGON (FINISHED-FULL) NUT SERIES	
N-5K	1/4-20	7/16"	15/64"	1/2"		
N-6K	1/4-28					
N-7K	1/4-20	7/16"	17/64"	1/2"		
N-8K	1/4-28					
N-9K	5/16-18	1/2"	21/64"	37/64"		
N-10K	5/16-24					
N-11K	3/8-16	9/16"	25/64"	5/8"		
N-12K	3/8-24					

P.C. 175

STAINLESS STEEL



Assembled "K-LOK" Locknuts



Inch Sizes

PRE-ASSEMBLED NUTS AND EXTERNAL LOCKWASHERS.
LOCKWASHERS FREE TO TURN BUT CANNOT DROP OFF.

SPAENAUR No.	THREAD SIZE	18-8 STAINLESS STEEL (For Hex. Nut part of Assembly)		AISI-410-420 STAINLESS STEEL (For Toothed Lockwasher of Assembly)		SERIES	PKG. 100
		WIDTH ACROSS FLATS	OVERALL THICKNESS	O.D. OF LOCKWASHER			
175-800	4-40	1/4"	7/64"	17/64"	STANDARD MACHINE SCREW NUT SERIES UNIT		
175-801	5-40	5/16"	9/64"	11/32"			
175-802	6-32	5/16"	9/64"	11/32"			
175-803	8-32	11/32"	5/32"	3/8"			
175-804	10-24	3/8"	5/32"	13/32"			
175-805	10-32						
175-806	1/4-20	7/16"	15/64"	1/2"	▲See above.		
175-807	1/4-28						
175-808	3/8-16	9/16"	25/64"	21/32"			

CATALOG 13


UNI-TORQUE LOCKNUT

SPAENAUR No. 165-100

Steel - Cad. Plated

7/16"-14 Thread

11/16" A.F. 23/64" Thick.



Unit
Package
100