




### CLAMPING COLLARS with screw

ONE  
PIECE

Clamping design fully engages the shaft without marring or other shaft damage. Effective on hard and soft shafts.

Full range of sizes available from 1/8" to 3" dia. shaft. (Min. qty. purchase may apply.)

SPAENAUR No.			▲Mild Steel Black Oxide Finish			*Tolerance +.003"/-.000"
▲STEEL	STAINLESS STEEL	ALUMINUM	*Bore Inch	O.D. Inch	Width Inch	Replacement Hex Socket Cap Screw Size
600-001	—	—	3/8	7/8	3/8	6-32 x 3/8"
600-002	—	—	1/2	1-1/8	13/32	8-32 x 1/2"
600-003	—	—	5/8	1-5/16	7/16	10-32 x 1/2"
600-004	—	—	3/4	1-1/2	1/2	1/4"-28 x 5/8"
600-005	—	—	7/8	1-5/8	1/2	1/4"-28 x 5/8"
600-006	—	—	1	1-3/4	1/2	1/4"-28 x 5/8"
600-007	—	—	1-1/4	2-1/16	1/2	1/4"-28 x 3/4"
600-008	—	—	1-3/8	2-1/4	9/16	1/4"-28 x 3/4"
600-009	—	—	1-1/2	2-3/8	9/16	1/4"-28 x 3/4"



### CLAMPING COLLARS with screws

TWO  
PIECE

Two piece collars may be easily installed where major disassembly would otherwise be necessary.

Clamping design fully engages the shaft without marring or other shaft damage. Effective on hard and soft shafts.

Full range of sizes available from 1/8" to 6" dia. shaft. (Min. qty. purchase may apply.)

SPAENAUR No.			▲Mild Steel Black Oxide Finish			*Tolerance +.003"/-.000"
▲STEEL	STAINLESS STEEL	ALUMINUM	*Bore Inch	O.D. Inch	Width Inch	Replacement Hex Socket Cap Screw Size
600-050	—	—	3/8	7/8	3/8	6-32 x 3/8"
600-051	—	—	1/2	1-1/8	13/32	8-32 x 1/2"
600-052	—	—	5/8	1-5/16	7/16	10-32 x 1/2"
600-053	—	—	3/4	1-1/2	1/2	1/4"-28 x 5/8"
600-054	—	—	7/8	1-5/8	1/2	1/4"-28 x 5/8"
600-055	—	—	1	1-3/4	1/2	1/4"-28 x 5/8"
600-056	—	—	1-1/4	2-1/16	1/2	1/4"-28 x 3/4"
600-057	—	—	1-3/8	2-1/4	9/16	1/4"-28 x 3/4"
600-058	—	—	1-1/2	2-3/8	9/16	1/4"-28 x 3/4"
600-059	—	—	2	3	11/16	5/16"-24 x 1"



ONE  
PIECE

Clamping design fully engages the shaft thread for secure locking. Adjusts easily.

More Climax items on E128 and E129.

### THREADED CLAMPING COLLARS with screw

Full range of sizes available 10-32 thru 2"-12. (Min. qty. purchase may apply.)

SPAENAUR No.		Bore	O.D.	Width	Replacement Hex
▲STEEL	STAINLESS STEEL	Thread	Inch	Inch	Socket Cap Screw Size
600-070	—	10-32	11/16	5/16	4-40 x 3/8"
600-071	—	1/4"-20	11/16	5/16	4-40 x 3/8"
600-072	—	1/4"-28	11/16	5/16	4-40 x 3/8"
600-075	—	5/16"-18	11/16	5/16	4-40 x 3/8"
600-073	—	5/16"-24	11/16	5/16	4-40 x 3/8"
600-074	—	3/8"-16	7/8	3/8	6-32 x 3/8"
600-079	—	3/8"-24	7/8	3/8	6-32 x 3/8"
600-076	—	1/2"-13	1-1/8	13/32	8-32 x 1/2"
600-080	—	1/2"-20	1-1/8	13/32	8-32 x 1/2"
600-081	—	5/8"-11	1-5/16	7/16	10-32 x 1/2"
600-077	—	5/8"-18	1-5/16	7/16	10-32 x 1/2"
600-082	—	3/4"-10	1-1/2	1/2	1/4"-28 x 5/8"
600-083	—	7/8"-9	1-5/8	1/2	1/4"-28 x 5/8"
600-078	—	1"-8	1-3/4	1/2	1/4"-28 x 5/8"

▲Mild Steel  
Black Oxide  
Finish

CATALOG 13

Please call for quotation.

All items this page Priced Singly.

Technical information on E129.

Stainless Steel and Aluminum, where shown, available upon request.

Minimum qty. purchase may apply.

Tel: 1-800-265-8772 Fax: 519-744-0818

E127