

# D1300 Retaining Rings

## Internal Type

### Carbon Spring Steel – Plain Finish


**DIN 472**

CHART CONTINUED FROM PREVIOUS PAGE  
See page E150 for Metric Retaining Ring Pliers  
and Assortment 805-442.

**NOTE:** Bore sizes to 300 mm, also additional in-between sizes  
may be available. Delivery usually 8-10 weeks on unlisted sizes.

SPAENAUR No.	A.D.I. Part No.	Bore (B) Diameter (mm)	Groove (G) Diameter (mm)	Groove Tolerance (mm)	Width (W) (min.) (mm)	Ring Thick. (T) (max.) (mm)	Unit Package Quantity
▲254-566YZ	—	56	59.0	+0.30	2.15	2.00	50
254-530	D1300—58	58	61.0	+0.30	2.15	2.00	50
254-531	D1300—60	60	63.0	+0.30	2.15	2.00	50
254-532	D1300—62	62	65.0	+0.30	2.15	2.00	50
254-567	—	63	66.0	+0.30	2.15	2.00	50
254-533	D1300—65	65	68.0	+0.30	2.65	2.50	50
254-534	D1300—68	68	71.0	+0.30	2.65	2.50	50
254-535	D1300—70	70	73.0	+0.30	2.65	2.50	50
254-536	D1300—72	72	75.0	+0.30	2.65	2.50	50
254-537	D1300—75	75	78.0	+0.35	2.65	2.50	50
254-538	D1300—78	78	81.0	+0.35	2.65	2.50	50
254-539	D1300—80	80	83.5	+0.35	2.65	2.50	50
254-540	D1300—82	82	85.5	+0.35	2.65	2.50	50
254-541	D1300—85	85	88.5	+0.35	3.15	3.00	50
254-542	D1300—88	88	91.5	+0.35	3.15	3.00	50
254-543	D1300—90	90	93.5	+0.35	3.15	3.00	50
254-544	D1300—92	92	95.5	+0.35	3.15	3.00	25
254-545	D1300—95	95	98.5	+0.35	3.15	3.00	25
254-546	D1300—98	98	101.5	+0.35	3.15	3.00	25
254-547	D1300—100	100	103.5	+0.35	3.15	3.00	25
254-568	—	102	106.0	+0.54	4.15	4.00	25
254-548	D1300—105	105	109.0	+0.54	4.15	4.00	25
254-569	—	107	—	+0.54	4.15	4.00	25
254-549	D1300—110	110	114.0	+0.54	4.15	4.00	10
254-571	—	112	116.0	+0.54	4.15	4.00	10
254-550	D1300—115	115	119.0	+0.54	4.15	4.00	10
254-551	D1300—120	120	124.0	+0.63	4.15	4.00	10
254-552	D1300—125	125	129.0	+0.63	4.15	4.00	10
254-553	D1300—130	130	134.0	+0.63	4.15	4.00	10
254-572	—	135	139.0	+0.63	4.15	4.00	1
254-557	—	140	144.0	+0.63	4.15	4.00	1
254-573	—	145	149.0	+0.63	4.15	4.00	1
254-574	—	150	155.0	+0.63	4.15	4.00	1
254-575	—	155	160.0	+0.63	4.15	4.00	1
254-576	—	160	165.0	+0.63	4.15	4.00	1
254-577	—	165	170.0	+0.63	4.15	4.00	1
254-580	—	170	175.0	+0.63	4.15	4.00	1
254-554	—	180	185.0	+0.72	4.15	4.00	1
254-581	—	225	231.0	+0.72	5.15	5.00	1

▲Yellow Zinc Plated