






Crimp 'N Seal®

Waterproof HEAT SHRINK Connectors

Crimp 'N Seal® waterproof connectors provide an environmental seal and offer superior strain relief. When heat is applied, the tough polymer jacket shrinks while simultaneously activating the adhesive inside the tubing to completely encapsulate the connection.

Easy Installation steps:



Electric Heat Gun

115 VOLTS AC

Two temperature settings 750°F & 1100°F. Cool down time not required. Fold down stand for hands free operation.



SPAENAUR No. 876-194

Priced Singly

Power Torch Portable Butane Heat Tool



Overall Height 5-3/4"


Priced Singly

Ideal for heat shrinkable connectors and tubing, soldering, and a variety of other applications. This versatile heat tool is fast and light weight, and will stand alone for hands-free operation. The self-igniting torch uses butane fuel, and is refillable. The tank capacity provides approximately 70 minutes of continuous usage. Two special attachments are included for use with heat shrinkable products.


SPAENAUR No. 876-1574



Heat Shrink Tubing




Heat Shrink Connectors



Soldering

(Butane not included.)

Crimp 'N Seal® Waterproof HEAT SHRINK Connector Rings



SPAENAUR No.	Wire Range	Stud Size	"B"	"W"	"L"	Max. Wire Insulation	Unit Pkg.
622-001	22-18	6	.250"	.25"	1.06"	.170"	10
622-002	22-18	10	.250"	.31"	1.08"	.170"	10
622-003	16-14	6	.250"	.31"	1.00"	.190"	10
622-004	16-14	8	.250"	.31"	1.03"	.190"	10
622-005	16-14	10	.250"	.31"	1.03"	.190"	10
622-006	16-14	1/4"	.250"	.46"	1.27"	.190"	10
622-007	16-14	5/16"	.250"	.46"	1.27"	.190"	10
622-008	16-14	3/8"	.250"	.53"	1.30"	.190"	10
622-009	12-10	8	.250"	.37"	1.22"	.240"	10
622-010	12-10	10	.250"	.37"	1.20"	.240"	10
622-011	12-10	1/4"	.250"	.52"	1.41"	.240"	10
622-012	12-10	3/8"	.250"	.59"	1.47"	.240"	10
622-013	12-10	1/2"	.250"	.72"	1.54"	.240"	10

CATALOG 13