

GASKETING & SEALING

Loctite has revolutionized the sealing of flanges in the automotive industry, in the assembly of heavy equipment and in the manufacture of various types of fluid power equipment.

A leader in form-in-place gasket makers, gasket dressings and general purpose sealants, Loctite offers a choice of anaerobics, RVT Silicones or solvents-based products to meet broad gasketing and sealing needs.

Instant Gasket

Makes high-performance, leakproof gaskets in one minute. Equipment can be returned to service immediately. Blowout resistant. Outperforms precut gaskets.

598 Black High Performance RVT Silicone Gasket Maker

Retains high flexibility and oil resistance for longer gasket life. Temperature range -75°F to 625°F (-59°C to 329°C) intermittent. Low odour, non-corrosive, low volatility. Resistant to most chemicals and solvents. Fills gaps to .25".

587 Blue High Performance RVT Silicone Gasket Maker

Forms tough, flexible gaskets directly on the flange. Offers excellent adhesion to oily surfaces. Low odour, non-corrosive, low volatility. Withstands temperatures to 500°F (260°C) intermittent. Resistant to most chemicals and solvents. Fills gaps to .25".

592 Copper High Performance RVT Silicone Gasket Maker

Premium silicone that can withstand operating environments to 700°F (371°C) intermittent. Superior oil resistance. Low odour, non-corrosive, low volatility, non-conductive. Resistant to most chemicals and solvents. Fills gaps to .25".

Superflex™ Blue RTV Silicone Adhesive Sealant

Cures to a tough, flexible rubber. Makes reliable "formed-in-place" gaskets that resist shrinking, cracking and migrating. Coats precut gaskets to increase reliability. Temperature range -65°F to 500°F (-54°C to 260°C) intermittent. Low volatility. Fills gaps to .25".

Superflex™ Red High Temp Silicone Adhesive Sealant

Makes gaskets that resist temperatures to 600°F (315°C) intermittent. Resists aging, weather and thermal cycling without shrinking, cracking, or hardening. Fills gaps to .25".

518 Gasket Eliminator® Flange Sealant

Forms a flexible, solvent-resistant seal that will not tear or decay. Seals to 300°F and fills gaps to 0.050". Can be used on flexible metal assemblies including aluminum surfaces. Easy disassembly and cleaning.

Q