



LUBRICANTS (ANTI-SEIZE)

A variety of penetrants, greases, oils and anti-seize formulas are available for lasting, general purpose lubrication or specific applications.

Anti-seize compounds protect mated metal parts against friction, galling and corrosion.

Anti-seize compounds also reduce wrench torque to facilitate assembly and disassembly of threaded connections.

Super Lube® synthetic-based lubricants last four times longer than traditional petroleum-based greases and work in high and low temperatures, food grade and multi-purpose applications.

C5-A® Copper Based Anti-Seize

Exclusive formula suspends copper and graphite in a high-quality grease. Protects metal parts from rust, corrosion, galling and seizing at temperatures to 1800°F (982°C). Tested to MIL-A-907.

Silver Grade Anti-Seize

Heavy duty, temperature-resistant, petroleum-based lubricant compound fortified with graphite and metallic flake. Inert, will not evaporate or harden in extreme cold or heat. For use in assemblies up to 1600°F (871°C).

Nickel Anti-Seize

Copper-free. Recommended for stainless steel and other metal fittings. For preventing corrosion, seizing and galling in harsh, chemical environments, and temperatures to 2400°F (1315°C).

Penetrating Oil

Penetrates, lubricates and displaces moisture. Protects against rust and corrosion. Contains no ODCs.

Super Lube® Synthetic-Based Lubricant with PTFE Grease

Lasts four times longer than petroleum-based lubricants. Withstands temperatures from -45°F to 450°F (550°F intermittent). Contains PTFE for added protection against friction and wear. Non-flammable (aerosol is flammable). Contains no ODCs. NLGI #2 grease. Translucent white to slightly yellow.