



THREADLOCKING

Invented by Loctite Corporation as a revolutionary method to lock and seal threaded fasteners. Loctite® Liquid Threadlockers have found wide acceptance in a range of applications—from delicate electronic components to heavy construction equipment. Loctite® Threadlockers are available in varying viscosities and strengths for virtually any application, including exposure to extreme environments.

222MS Threadlocker Low Strength/Small Screw

Ideal for fastener diameters of 1/4" (6 mm) and smaller. Controlled lubricity for accurate clamp loads. Parts can be separated using hand tools.

242® Threadlocker Medium Strength

A general-purpose, removable threadlocker for fasteners between 1/4" and 3/4" (6 to 20 mm) diameters. Controlled lubricity for accurate clamp loads. Parts can be separated using hand tools.

243 Threadlocker Oil Resistant/Medium Strength

A general-purpose, medium strength threadlocker with improved oil tolerance. For fasteners between 1/4" and 3/4" (6 to 20 mm) diameters.

262 Threadlocker Medium to High Strength

A permanent locking threadlocker for fasteners up to 3/4" (20 mm) diameter. High lubrication for easy assembly. Excellent for preventing rust and corrosion in extreme chemical/environmental conditions.

277 Threadlocker High Strength

Locks fasteners up to 1-1/2" (36 mm). Protects threads from rust and corrosion. Removable with heat and hand tools.

290 Threadlocker Wicking Grade

A medium-strength threadlocker for pre-assembled bolts up to 1/2" (12 mm). Penetrates threads by capillary action. Secures set screws and other assemblies after settings are completed. Seals welds and porous metal parts. Protects threads from rust and corrosion. Localized heating and hand tools are needed for disassembly.

425 Assure™ Threadlocker Surface Curing

Low strength, fast curing threadlocker for plastic fasteners. Can be applied before or after assembly.

NOTE:

To ensure safe transport, all Loctite® products are shipped via ground. To inquire about specific delivery times for your area, please contact a Spaenaur Sales Representative at 1-800-265-8772.

Afin d'assurer l'absence de risques dans la transportation des produits Loctite® l'expédition sera effectuée par la mode de terre. Afin de vous renseigner des heures spécifiques de livraison dans votre région, veuillez communiquer avec votre représentant de ventes Spaenaur au 1-800-265-8772.