

Battery Terminal Lugs

Inch

Bornes de batterie

Pouce

Post Top Battery Terminals

Copper construction provides a low resistance connection while tin plating offers extended life in non-gaseous environments. Cable size, polarity, and tool die codes are in raised characters for increased legibility.

Tin Plate Straights



SPAENAUR No.	Cable Size	Polarity	Tool Die Codes	PKG QTY.
622-200	4	NEGATIVE	GREEN J-H	1
622-201	4	POSITIVE	GREEN J-H	1
622-203	4	UNIVERSAL	GREEN J-H	1
622-204	1-2	NEGATIVE	PINK H-H	1
622-205	1-2	POSITIVE	PINK H-H	1
622-206	1/0	NEGATIVE	BLACK E-A	1
622-207	1/0	POSITIVE	BLACK E-A	1
622-208	2/0	NEGATIVE	ORANGE A-C	1
622-209	2/0	POSITIVE	ORANGE A-C	1
622-210	3/0	NEGATIVE	PURPLE A-B	1
622-211	3/0	POSITIVE	PURPLE A-B	1
622-212	4/0	NEGATIVE	YELLOW A-A	1
622-213	4/0	POSITIVE	YELLOW A-A	1



Tin Plated Right Elbows

SPAENAUR No.	Cable Size	Polarity	Tool Die Codes	PKG QTY.
622-214	1/0	NEGATIVE	BLACK E-A	1
622-215	1/0	POSITIVE	BLACK E-A	1
622-216	2/0	NEGATIVE	ORANGE A-C	1
622-217	2/0	POSITIVE	ORANGE A-C	1
622-218	3/0	NEGATIVE	PURPLE A-B	1
622-219	3/0	POSITIVE	PURPLE A-B	1
622-220	4/0	NEGATIVE	YELLOW A-A	1
622-221	4/0	POSITIVE	YELLOW A-A	1



Tin Plated Left Elbows

SPAENAUR No.	Cable Size	Polarity	Tool Die Codes	PKG QTY.
622-222	1/0	NEGATIVE	BLACK E-A	1
622-223	1/0	POSITIVE	BLACK E-A	1
622-224	2/0	NEGATIVE	ORANGE A-C	1
622-225	2/0	POSITIVE	ORANGE A-C	1
622-226	3/0	NEGATIVE	PURPLE A-B	1
622-227	3/0	POSITIVE	PURPLE A-B	1
622-228	4/0	NEGATIVE	YELLOW A-A	1
622-229	4/0	POSITIVE	YELLOW A-A	1

G

Inch

Battery Terminal Lugs & Connectors

Pouce

Cosses et connecteurs de bornes de batterie



Post Top Battery Terminals

Tin Plated Flags

SPAENAUR No.	Cable Size	Polarity	Tool Die Codes	PKG QTY.
622-230	1/0	NEGATIVE	BLACK E-A	1
622-231	1/0	POSITIVE	BLACK E-A	1
622-232	2/0	NEGATIVE	ORANGE A-C	1
622-233	2/0	POSITIVE	ORANGE A-C	1
622-234	3/0	NEGATIVE	PURPLE A-B	1
622-235	3/0	POSITIVE	PURPLE A-B	1
622-236	4/0	NEGATIVE	YELLOW A-A	1
622-237	4/0	POSITIVE	YELLOW A-A	1

Stud Top Battery Terminals

Copper, Crimp-Type, Tin Plated

Copper construction provides a low resistance connection, while tin plating offers extended life in non-gaseous environments. Cable size, polarity, and tool die codes are in raised characters for increased legibility.



Tin Plated Terminal

SPAENAUR No.	Cable Size	Polarity	Tool Die Codes	PKG QTY.
622-238	4	UNIVERSAL	GREEN J-H	1
622-239	1	UNIVERSAL	PINK H-H	1
622-240	1/0	UNIVERSAL	BLACK E-A	1
622-241	2/0	UNIVERSAL	ORANGE A-C	1
622-242	3/0	UNIVERSAL	PURPLE A-B	1
622-243	4/0	UNIVERSAL	YELLOW A-A	1

Tin Plated Splice (Double)



SPAENAUR No.	Cable Size	Polarity	Tool Die Codes	PKG QTY.
622-244	1/0	UNIVERSAL	BLACK E-A	1
622-245	2/0	UNIVERSAL	ORANGE A-C	1
622-246	3/0	UNIVERSAL	PURPLE A-B	1
622-247	4/0	UNIVERSAL	YELLOW A-A	1

CATALOG 14

SPAENAUR

G

Electrical Wire Terminal Lugs / Splice Connectors

Inch

Cosses de conducteurs électriques / Connecteurs d'épissures

Pouce



Starter Lugs & Splices - Copper

Heavy Duty Power Lug - Tin Plated




Increased wall thickness yields greater strength and conductivity. Tin plating offers corrosion resistance. Crimps with the same die setting as corresponding size battery terminal.



SPAENAUR No.	Cable Size	Stud Size	"B"	"L"	"W"	PKG QTY.
622-248	1/0	3/8"	.583"	2.00"	.84"	5
622-249	1/0	1/2"	.583"	2.00"	.84"	5
622-250	2/0	3/8"	.640"	2.25"	.91"	5
622-251	2/0	1/2"	.640"	2.25"	.91"	5
622-252	3/0	3/8"	.715"	2.25"	1.03"	5
622-253	3/0	1/2"	.715"	2.25"	1.03"	5
622-254	4/0	3/8"	.780"	2.40"	1.14"	5
622-255	4/0	1/2"	.780"	2.40"	1.14"	5

G

Starter Lugs Light Duty Lugs (Unplated)



SPAENAUR No.	Cable Size	Stud Size	"B"	"L"	"W"	PKG QTY.
622-256	6	1/4"	.232"	1.32"	.54"	10
622-257	6	3/8"	.232"	1.32"	.54"	10
622-258	6	1/2"	.232"	1.32"	.54"	10
622-259	4	1/4"	.286"	1.51"	.56"	10
622-260	4	5/16"	.286"	1.51"	.56"	10
622-261	4	3/8"	.286"	1.51"	.56"	10
622-262	2	1/4"	.336"	1.61"	.64"	10
622-263	2	3/8"	.336"	1.61"	.64"	10
622-264	1	1/4"	.360"	1.72"	.645"	10
622-265	1	3/8"	.360"	1.72"	.645"	10
622-266	1	1/2"	.360"	1.72"	.645"	10
622-267	1/0	3/8"	.407"	1.82"	.725"	10
622-268	1/0	1/2"	.407"	1.82"	.745"	10
622-269	2/0	3/8"	.461"	2.04"	.82"	10
622-270	2/0	1/2"	.461"	2.04"	.82"	10
622-271	3/0	3/8"	.511"	2.20"	.970"	10
622-272	3/0	1/2"	.511"	2.20"	.970"	10
622-273	4/0	3/8"	.559"	2.45"	1.09"	10
622-274	4/0	1/2"	.625"	2.45"	1.09"	10

Cable Splices Tin Plated



SPAENAUR No.	Cable Size	"B"	"D"	"L"	PKG QTY.
622-275	6	.232"	.312"	1.078"	5
622-276	4	.286"	.375"	1.219"	5
622-277	2	.336"	.437"	1.344"	5
622-278	1	.360"	.465"	1.344"	5
622-279	1/0	.407"	.515"	1.630"	5
622-280	2/0	.461"	.570"	1.797"	5
622-281	3/0	.511"	.630"	1.906"	5
622-282	4/0	.590"	.720"	2.000"	5