

Bungee Hooks / Rings / Toggles

Inch and Metric

Crochets pour tendeurs élastiques / Bagues / Interrupteurs à bascule

Pouce et Métrique

PKG QTY. 10		
SPAENAUR No.	USE WITH CORD DIA. Inches	mm
PLASTIC COATED HOOKS & RINGS		
121-C19-1T	3/16	5 mm
121-C05-1C	1/4	6 mm
121-C20-1N	5/16	8 mm
121-C21-1T	3/8	9 mm
121-C22-1K	13/32	10 mm
121-C23-1W	1/2	12 mm
121-C10-1K	1/2	12 mm
DICHROMATED HOOKS & RINGS		
121-C24-1M	5/32	4 mm
121-C25-1X	3/16	5 mm
121-C26-1A	1/4	6 mm
121-C27-1P	5/16	8 mm
121-C28-1Y	3/8	9 mm
121-C29-1C	13/32	10 mm
121-C30-1Y	1/2	12 mm
DICHROMATED HOOKS ONLY		
121-C11-1W	5/32	4 mm
121-C12-1M	3/16	5 mm
121-C14-1A	5/16	8 mm
121-C15-1P	3/8	9 mm
121-C16-1Y	13/32	10 mm
STAINLESS STEEL HOOKS & RINGS		
121-C45-1T	3/16	5 mm
121-C48-1M	1/4	6 mm
121-C50-1M	5/16	8 mm
121-C52-1A	3/8	9 mm
121-C55-1C	13/32	10 mm
121-C57-1T	1/2	12 mm



PLASTIC BALL			
SPAENAUR No.	DIAMETER Inches	mm	PKG QTY.
122-A02-1X	1"	25 mm	10
STRETCH NET HOOKS			
SPAENAUR No.	LENGTH	PKG QTY.	
122-012	Large	5-1/2"	10
'C' RING			
SPAENAUR No.	MATERIAL	FITS CORD DIA. SIZE	PKG QTY.
121-C01-1X	Galvanized Steel	4 & 5 mm	10
121-C03-1P	Galvanized Steel	6 to 9 mm	25
121-C18-1N	Galvanized Steel	10 to 12 mm	10
121-C54-1Y	Stainless Steel	10 & 12 mm	25



WARNING Cords are to hold or tie together masses of varying sizes and weights. It is important to use good judgement in choosing appropriate cord lengths and diameters for the intended purpose. **EXTREME CAUTION** should be taken when cords are stretched. Ends of stretched cords should be held firmly and fastened securely. Care should be taken that face and other vulnerable body parts are kept away from potential cord rebound path. Do not attempt to stretch a cord beyond obvious limits. Generally, most effective stretch range is 75% beyond unstretched length.

AVERTISSEMENT Les cordes sont destinées à lier ensemble ou attacher des articles de différents poids ou tailles. Il est très important d'utiliser un bon jugement pour choisir les cordes de diamètres ou de tailles appropriés. **D'EXTRÊMES PRECAUTIONS** Doivent être prises lorsque l'on tire les cordes, bien tenir en main les extrémités et s'assurer que la fixation est correcte. Tenir à l'écart d'un possible rebondissement de la corde, la figure ou toute autre partie vulnérable du corps. Ne pas essayer de tirer la corde au delà de ses limites. En general l'élasticité la plus efficace est d'environ 75% au delà de la taille originat.

See Page M23 for T-Plastech Cord-Lok®



Inch

Elastic Shockcord & Attachment / Mounts / Hooks

Pouce

Cordon élastique et attaches / supports / crochets

SHOCKCORD MOUNTS
Tough Delrin 500 (Black)
For use with 1/4" dia. Shockcord

SPAENAUR No.	Style	Type of End	PKG QTY.
122-410	A	For 1" Webbing	10
122-413	B	Has 3/16" hole	10
122-416	C	Hook, with tongue	10

Note: Elastic Cord should be tight-wrapped with 1" wide masking tape, 1-1/4 turns. Then cut through the wrapped part with a sharp knife or shears. This yields non-fraying ends, for secure anchoring in the mount.

EASY HOOK
(Natural Nylon)

SPAENAUR No. 122-420

Hook Opening .153"

Non-conductive, rust resistant, and can be used with "D" and "O" rings.
For use with 1/8" dia. Shockcord.

PKG QTY. 50

Adjustable SHOCKCORD HOOK
For use with 1/4" dia. Shockcord
Material: Acetal Colour: Black
PKG QTY. 10

Adjustable CORD HOOK
SPAENAUR No. 122-445

For use with 1/8" to 1/4" dia. Shockcord.
Snaphook opening to 1/4" dia. max.
Material: Nylon Colour: Black
PKG QTY. 10

ELASTIC SHOCKCORD
Strong and durable.

CHOOSE FROM COTTON OR NYLON COVERING.

SPAENAUR No.	COTTON COVERING		NYLON COVERING	
	Cord Dia.	Spool Size	Cord Dia.	Spool Size
810-009	1/8"	1,000 ft.	810-051	1/8"
MP-82	3/16"	1,000 ft.	810-052	5/32"
MP-44	1/4"	500 ft.	810-053	3/16"
MP-45	5/16"	500 ft.	810-054	1/4"
MP-46	3/8"	300 ft.	810-055	5/16"
MP-47	7/16"	250 ft.	*810-010	5/16"
MP-48	1/2"	150 ft.	810-056	3/8"
			810-057	7/16"
			810-058	1/2"

ELASTIC CORD LOAD AND STRETCH DATA

Dia.	Stretch	Load 100%	Approx. Breaking Strength
3/16"		12 lbs.	75 lbs.
1/4"	6" to 12"	20 lbs.	127 lbs.
5/16"	6" to 12"	55 lbs.	175 lbs.
3/8"	6" to 12"	60 lbs.	520 lbs.
7/16"	6" to 12"	65 lbs.	575 lbs.
1/2"	6" to 12"	70 lbs.	610 lbs.

*All Black Cover
- Covering Colour -
White with Coloured Fleck.

SHOCKCORD ATTACHMENTS
Available in Plated Steel and 302 Stainless Steel

Hook is first slid over end of cord. Ring is then clamped to end of cord with pliers. Hook then engages ring, and will not come off. Hook completely covers retaining ring.

PKG QTY. 25

High Tensile STEEL - Zinc Plated

Complete Attachment	Spring Hook Only	Retainer Ring Only
MH-90 (for 3/16" shockcord)	121-213	121-218
MH-1 (for 1/4" shockcord)	121-214	121-219
MH-2 (for 5/16" shockcord)	121-215	121-220
MH-91 (for 3/8" shockcord)	121-216	121-221
MH-3 (for 7/16" and 1/2" cord)	121-217	121-222

302 STAINLESS STEEL

Complete Attachment	Spring Hook Only	Retainer Ring Only
MH-90SS (for 3/16" shockcord)	121-823	121-828
MH-1SS (for 1/4" shockcord)	121-824	121-829
MH-2SS (for 5/16" shockcord)	121-825	121-830
MH-91SS (for 3/8" shockcord)	121-826	121-831
MH-3SS (for 7/16" and 1/2" cord)	121-827	121-832

CATALOG 14 SPAENAUR