

Electrical Wire Terminal Lugs / Splice Connectors

Inch

Cosses de conducteurs électriques / Connecteurs d'épissures

Pouce



Starter Lugs & Splices - Copper

Heavy Duty Power Lug - Tin Plated




Increased wall thickness yields greater strength and conductivity. Tin plating offers corrosion resistance. Crimps with the same die setting as corresponding size battery terminal.



SPAENAUR No.	Cable Size	Stud Size	"B"	"L"	"W"	PKG QTY.
622-248	1/0	3/8"	.583"	2.00"	.84"	5
622-249	1/0	1/2"	.583"	2.00"	.84"	5
622-250	2/0	3/8"	.640"	2.25"	.91"	5
622-251	2/0	1/2"	.640"	2.25"	.91"	5
622-252	3/0	3/8"	.715"	2.25"	1.03"	5
622-253	3/0	1/2"	.715"	2.25"	1.03"	5
622-254	4/0	3/8"	.780"	2.40"	1.14"	5
622-255	4/0	1/2"	.780"	2.40"	1.14"	5

G

Starter Lugs Light Duty Lugs (Unplated)



SPAENAUR No.	Cable Size	Stud Size	"B"	"L"	"W"	PKG QTY.
622-256	6	1/4"	.232"	1.32"	.54"	10
622-257	6	3/8"	.232"	1.32"	.54"	10
622-258	6	1/2"	.232"	1.32"	.54"	10
622-259	4	1/4"	.286"	1.51"	.56"	10
622-260	4	5/16"	.286"	1.51"	.56"	10
622-261	4	3/8"	.286"	1.51"	.56"	10
622-262	2	1/4"	.336"	1.61"	.64"	10
622-263	2	3/8"	.336"	1.61"	.64"	10
622-264	1	1/4"	.360"	1.72"	.645"	10
622-265	1	3/8"	.360"	1.72"	.645"	10
622-266	1	1/2"	.360"	1.72"	.645"	10
622-267	1/0	3/8"	.407"	1.82"	.725"	10
622-268	1/0	1/2"	.407"	1.82"	.745"	10
622-269	2/0	3/8"	.461"	2.04"	.82"	10
622-270	2/0	1/2"	.461"	2.04"	.82"	10
622-271	3/0	3/8"	.511"	2.20"	.970"	10
622-272	3/0	1/2"	.511"	2.20"	.970"	10
622-273	4/0	3/8"	.559"	2.45"	1.09"	10
622-274	4/0	1/2"	.625"	2.45"	1.09"	10

Cable Splices Tin Plated



SPAENAUR No.	Cable Size	"B"	"D"	"L"	PKG QTY.
622-275	6	.232"	.312"	1.078"	5
622-276	4	.286"	.375"	1.219"	5
622-277	2	.336"	.437"	1.344"	5
622-278	1	.360"	.465"	1.344"	5
622-279	1/0	.407"	.515"	1.630"	5
622-280	2/0	.461"	.570"	1.797"	5
622-281	3/0	.511"	.630"	1.906"	5
622-282	4/0	.590"	.720"	2.000"	5