


Cutting / Grinding Wheels

Roues de coupage / meulage



Inch
Pouce

NEW



APPLICATIONS
Steel
Rebar
Bar stock
Structural steel
All ferrous metals

STATIONARY CUT-OFF AND CHOPSAW WHEEL
Metal, Double Reinforced, Type 1

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM
876-F89-1Y	A1-11401191	14" x 1/8" x 1"	4365


FEATURES

- Aluminum Oxide grain
- High strength phenolic resin bond
- ISO 9001 Certified - Red color code
- Double external reinforced with high tensile strength fiberglass

BENEFITS

- Extended wheel life
- Strong, durable, long-lasting grain
- High strength for added safety

NEW



APPLICATIONS
Steel
Tubing
All ferrous metals
Structural shapes
Small solid bar stock
Light bar stock

LOW HORSEPOWER CHOP SAW WHEEL
Metal, Center Reinforced, Type 1

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM
876-F90-1P	A1-11401091	14" x 7/64" x 1"	4365


BENEFITS

- Extended wheel life
- Free and cool cutting
- Strong, durable long-lasting grain
- Less operator fatigue
- Less wear on chop saw

FEATURES

- Aluminum Oxide grain
- High strength phenolic resin bond
- Center reinforced with high tensile strength fiberglass
- Formulated for low horsepower portable, electric chop saws
- ISO 9001 Certified - Red color code

NEW



APPLICATIONS
Stainless steel
Alloy
Carbon steel
Metal tubing
Rebar
Light-gauge metals

PREMIUM THIN CUT-OFF WHEEL
Metal & Stainless Steel, Double Reinforced, Type 1

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM
876-F91-1Y	A3-10450251	4 1/2" x .040" x 7/8"	13580
876-F92-1C	A3-10450351	4 1/2" x .045" x 7/8"	13580
876-F93-1N	A3-10500251	5" x .040" x 7/8"	12225
876-F94-1T	A3-10500351	5" x .045" x 7/8"	12225
876-F95-1K	A3-10600251	6" x .040" x 7/8"	10190
876-F96-1W	A3-10600351	6" x .045" x 7/8"	10190


FEATURES

- Extra thin design
- Premium Aluminum Oxide grain
- ISO 9001 Certified - Red color code
- Double external reinforced with high tensile strength fiberglass

BENEFITS

- Fast cutting at less power
- Maximum safety
- Long life
- Cuts cooler and cleaner
- Cuts without vibrations or burns

NEW



APPLICATIONS
All ferrous metals
Steel/structural steel
Rebar
Welds
Pipe
Bar stock

T27 DEPRESSED CENTER GRINDING WHEEL
Metal, Type 27 Depressed Center

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM
876-F99-1A	A5-10451452	4 1/2" x 1/4" x 7/8"	13580
876-G01-1T	A5-10501452	5" x 1/4" x 7/8"	12225


FEATURES

- Aluminum Oxide grain
- Dual grit - Harder bond
- Available with 5/8"-11 threaded hub
- ISO 9001 Certified - Red color code
- Internally reinforced with layers of high tensile strength fiberglass

BENEFITS

- Aggressive material removal
- Strong, durable long-lasting grain
- Maximum safety
- Fast, easy spin on and off
- Longer life

NEW



APPLICATIONS
Stainless steel
Alloy
Carbon steel
Metal tubing
Rebar
Light-gauge metals

PREMIUM THIN CUT-OFF WHEEL
Metal & Stainless Steel, Double Reinforced, Type 27 Depressed Center

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM
876-F97-1M	A4-10450252	4 1/2" x .040" x 7/8"	13580
876-F98-1X	A4-10600252	6" x .040" x 7/8"	10190


FEATURES

- Extra thin design
- Premium Aluminum Oxide grain
- ISO 9001 Certified - Red color code
- Double external reinforced with high tensile strength fiberglass

BENEFITS

- Fast cutting at less power
- Maximum safety
- Long life
- Cuts cooler and cleaner
- Cuts without vibrations or burns

NEW



APPLICATIONS
All ferrous metals
Steel/structural steel
Rebar
Welds
Pipe
Bar stock

T27 DEPRESSED CENTER GRINDING WHEEL - FLANGED
Metal, Type 27 Depressed Center, Flanged

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM
876-G02-1K	A5-10451472	4 1/2" x 1/4" x 5/8"-11	13580
876-G03-1W	A5-10501472	5" x 1/4" x 5/8"-11	12225

FEATURES

- Aluminum Oxide grain
- Dual grit - Harder bond
- Available with 5/8"-11 threaded hub
- ISO 9001 Certified - Red color code
- Internally reinforced with layers of high tensile strength fiberglass

BENEFITS

- Aggressive material removal
- Strong, durable long-lasting grain
- Maximum safety
- Fast, easy spin on and off
- Longer life

P

Inch
Pouce



Grinding Wheels

Roues de meulage

NEW



APPLICATIONS
Rust removal
Light deburring
Ferrous and non-ferrous metals
Best for welds and blending
All purpose sanding and grinding

T29 STANDARD FLAP DISC - ZIRCONIA
4 1/2" x 7/8" - Standard

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM	Grit
876-G04-1M	F-4510409	4 1/2" x 7/8" T29	13,000	40
876-G05-1X	F-4510609	4 1/2" x 7/8" T29	13,000	60
876-G06-1A	F-4510809	4 1/2" x 7/8" T29	13,000	80
876-G07-1P	F-4511209	4 1/2" x 7/8" T29	13,000	120

FEATURES

- Heavy X-weight cloth
- Fiberglass backing
- Resin on resin bond
- With/without hub
- ISO 9001 Certified

BENEFITS

- Type 29 shape for maximum aggression
- High cut rate
- Fast and cool cutting
- Grind, blend, and finish in one easy step
- No need to switch from grinding wheel to resin fiber disc

NEW



APPLICATIONS
Rust removal
Light deburring
Ferrous and non-ferrous metals
Best for welds and blending
All purpose sanding and grinding

T29 HIGH DENSITY FLAP DISC - ZIRCONIA
4 1/2" x 5/8" -11 - High Density/Jumbo, Flanged

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM	Grit
876-G08-1Y	F-4540409HF	4 1/2" x 5/8" - 11 T29 Jumbo	13,000	40
876-G09-1C	F-4540609HF	4 1/2" x 5/8" - 11 T29 Jumbo	13,000	60
876-G10-1Y	F-4540809HF	4 1/2" x 5/8" - 11 T29 Jumbo	13,000	80
876-G11-1C	F-4541209HF	4 1/2" x 5/8" - 11 T29 Jumbo	13,000	120

FEATURES

- Heavy X-weight cloth
- Fiberglass backing
- Resin on resin bond
- With/without hub
- ISO 9001 Certified

BENEFITS

- Type 29 shape for maximum aggression
- High cut rate
- Fast and cool cutting
- Grind, blend, and finish in one easy step
- No need to switch from grinding wheel to resin fiber disc

NEW



APPLICATIONS
Rust removal
Light deburring
Ferrous and non-ferrous metals
Best for welds and blending
All purpose sanding and grinding

T27 STANDARD FLAP DISC - ZIRCONIA
4 1/2" x 7/8" - Standard

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM	Grit
876-G12-1N	F-4550367	4 1/2" x 7/8" T27	13,000	36
876-G13-1T	F-4550407	4 1/2" x 7/8" T27	13,000	40
876-G14-1K	F-4550607	4 1/2" x 7/8" T27	13,000	60
876-G15-1W	F-4550807	4 1/2" x 7/8" T27	13,000	80
876-G16-1M	F-4551207	4 1/2" x 7/8" T27	13,000	120

FEATURES

- Heavy X-weight cloth
- Fiberglass backing
- Resin on resin bond
- With/without hub
- ISO 9001 Certified

BENEFITS

- Type 27 shape for smooth grinding
- Fast and cool cutting
- Grind, blend, and finish in one easy step
- No need to switch from grinding wheel to resin fiber disc

NEW



APPLICATIONS
Rust removal
Light deburring
Ferrous and non-ferrous metals
Best for welds and blending
All purpose sanding and grinding

T27 HIGH DENSITY FLAP DISC - ZIRCONIA
4 1/2" x 5/8" -11 - High Density/Jumbo, Flanged

PKG QTY. 1

SPAENAUR No.	Mfg. No.	Size	Max RPM	Grit
876-G17-1X	F-4580407HF	4 1/2" x 5/8" - 11 T29	13,000	40
876-G18-1A	F-4580607HF	4 1/2" x 5/8" - 11 T29	13,000	60
876-G19-1P	F-4580807HF	4 1/2" x 5/8" - 11 T29	13,000	80
876-G20-1A	F-4581207HF	4 1/2" x 5/8" - 11 T29	13,000	120

FEATURES

- Heavy X-weight cloth
- Fiberglass backing
- Resin on resin bond
- With/without hub
- ISO 9001 Certified

BENEFITS

- Type 27 shape for smooth grinding
- Fast and cool cutting
- Grind, blend, and finish in one easy step
- No need to switch from grinding wheel to resin fiber disc



WARNING: Always use tools with guards & wear protective equipment.