


Tamper-Resistant Sheet Metal Screws / Tools

Vis à tôle inviolables / Outils



Inch and **Metric**
Pouce et **Métrique**

B



**A New Twist In
Tamper-Resistant Screws**

Type A

18-8 STAINLESS STEEL



The Opsit has a Tri-Wing® drive and low-profile Truss Head with a left-hand thread that tightens the screw with each **counter-clockwise** turn!

SPAENAUR No.	Type A Screw Size	Bit Size	PKG QTY.
516-1041	#8 x 1/2"	4	50
516-1042	#8 x 3/4"	4	50
516-1043	#8 x 1"	4	50
516-1046	#10 x 1/2"	5	50
516-C41-1Y	#10 x 3/4"	5	50
516-1048	#10 x 1"	5	50
516-1049	#10 x 1-1/4"	5	50
516-1050	#10 x 1-1/2"	5	50

Insert Bits for use with Tri-Wing® Screws above.

Not for use with power drivers.



Tri-Wing

Alloy Steel

Top Quality, extra hard (Grey)

1/4" hex shanks, 1" long.

See page P17 for Bit Driver Handles.

Bit Point Size	SPAENAUR No.
0	876-1631
1	876-218
2	876-1634
3	876-1635
4	876-1636
5	876-1637
6	876-1638

All Bits PKG QTY. 1

Metric Hex Socket Security Bits and Keys



All Bits & Keys
PKG QTY. 1

Bit Size Across Flats		Insert Bits			Hex Keys	
		SPAENAUR No.	Length and Hex Size		SPAENAUR No.	Lengths
2.5 mm		877-535	25 x 6.3 mm	-	-	
3 mm		877-536	25 x 6.3 mm	-	-	
4 mm		877-537	25 x 6.3 mm	877-C09-1Y	21 x 64 mm	
5 mm		877-538	25 x 6.3 mm	877-543	25 x 68 mm	
6 mm		877-539	25 x 6.3 mm	877-544	32 x 90 mm	

Hex keys have a hole in both ends.

For Tampruf Fasteners see Page B103

B116

© 2018 Spenaaur Inc. All rights reserved. Catalog may not be reproduced, in whole or in part, without the written permission of Spenaaur Inc. Subject to Catalog Terms and Conditions of Use available at Spenaaur.com and on page TC2 and TC3 at the back of this catalog.
© 2018 Spenaaur Inc. Tous droits réservés. Le catalogue ne peut être reproduit, en tout ou en partie, sans l'autorisation écrite de Spenaaur Inc. L'utilisation est soumise aux Conditions d'utilisation du Catalogue disponibles sur Spenaaur.com et à la page TC4 et TC5 à la fin de ce catalogue.