

# Threadlockers & Liquid Thread Sealants

Adhésifs frein-filet et scellants liquides pour filets



## NEW THREADLOCKER & THREAD SEALANT

Threadlocker prevents threaded fasteners from coming loose due to shock and vibration

### 121 MEDIUM STRENGTH THREADLOCKER

BLUE



**Removable Medium Strength** anaerobic threadlocker designed for locking threaded fasteners from 1/4" to 3/4" (6-20 mm) in diameter, that require disassembly with standard hand tools. Exhibits good temperature and solvent resistance.

SPAENAUR #	SIZE	LOCTITE® #	COLOUR
800-B80-1W	10ml	24221	BLUE
800-B81-1M	50ml	24231	BLUE

COMPETES WITH LOCTITE 242™

VISCOSITY (cP):	900 – 1500	TEMP RANGE:	-65°F to 300°F
MAX GAP FILL:	0.007 in	FIXTURE TIME:	15-20 min (at 72°F)
TORQUE (lbs) BREAK/PREV.	120/45	SPEC. GRAVITY:	1.00

### 140 HIGH STRENGTH THREADLOCKER

RED



**High Strength** anaerobic threadlocker for maximum security, designed to permanently lock fasteners up to 1" (25 mm) in diameter, that require disassembly with heat and hand tools. Suitable for most applications where disassembly is not required. Exhibits good temperature and solvent resistance. **Was designed for use with FINE threaded fasteners.**

SPAENAUR #	SIZE	LOCTITE® #	COLOUR
800-B84-1P	50ml	27131	RED

COMPETES WITH LOCTITE 271™

VISCOSITY (cP):	500	TEMP RANGE:	-65°F to 300°F
MAX GAP FILL:	0.007 in	FIXTURE TIME:	15-20 min (at 72°F)
TORQUE (lbs) BREAK/PREV.	250/275	SPEC. GRAVITY:	1.1

### 131 HIGH STRENGTH PERMANENT THREADLOCKER

RED



**High Strength Permanent** anaerobic threadlocker for maximum security, designed to permanently lock up to 1" (25 mm) in diameter, that require disassembly with heat and hand tools. Exhibits good temperature and solvent resistance. **Designed for use with COARSE threaded fasteners.**

SPAENAUR #	SIZE	LOCTITE® #	COLOUR
800-B82-1X	10ml	26221	RED
800-B83-1A	50ml	26231	RED

COMPETES WITH LOCTITE 262™

VISCOSITY (cP):	1200 - 2400	TEMP RANGE:	-65°F to 300°F
MAX GAP FILL:	0.007 in	FIXTURE TIME:	15-20 min (at 72°F)
TORQUE (lbs) BREAK/PREV.	200/250	SPEC. GRAVITY:	1.1

### 460 HIGH TEMPERATURE STAINLESS STEEL THREAD SEALANT

WHITE



**High Temperature** Stainless Steel thread Sealant, designed to fill the space between threaded metal parts, which sets fast to give an instant low pressure seal of 100 psi and a high pressure seal when fully cured. This high strength product provides 100% sealing capability and does not shrink after curing, unlike more traditional solvent based pipe dopes. For repairs, parts **may be disassembled with basic hand tools.** Contains PTFE.

SPAENAUR #	SIZE	LOCTITE® #	COLOUR
800-B85-1Y	50ml	56747	WHITE

COMPETES WITH LOCTITE 567™

VISCOSITY (cP):	Paste	FULL CURE TIME:	24 hrs (at 68°F)
MAX GAP FILL:	0.012 in	TEMP RANGE:	-65°F to 400°F

### RESEALABLE BULLET TUBES OF THREADLOCKER

Popular Vibra-TITE bullets conveniently sized for small projects. With this bullet, **you get more than just 1 shot**, providing up to 15 applications in each resealable tube.

**Bullet Tubes are perfect for small projects & Tool Kits!**

SPAENAUR #	SIZE	DESCRIPTION	COLOUR	COMPETES WITH LOCTITE® #
800-B89-1K	2ml	131 Permanent Strength	RED	262™
800-B86-1C	2ml	121 Medium Strength	BLUE	242™



SAFETY & TECHNICAL data sheets available online @ [spaenaur.com](http://spaenaur.com)