



Inch

Synthetic Rope / Elastic Cable / Cord Couplers

Pouce

Corde synthétique / Câble élastique / Raccords pour corde

 <p style="text-align: center;">Coil</p>	CORD DIAMETER		50 FT. COIL (15.25 m) POLY BAGGED	328 FT. (100 m) SPOOL
	MULTI-COLOR FIBERTEX		SPAENAUR No.	SPAENAUR No.
 <p style="text-align: center;">Spool</p> <p style="text-align: center;">Sold in Full Spools Only.</p> <p style="text-align: center;">(* 300 Ft. Spool)</p>	Inches	mm		
	5/32	4	810-250	810-B02-1P
	3/16	5	810-251	810-225
	1/4	6	810-252	810-226
	5/16	8	810-253	810-227
	3/8	9	810-254	810-228
	13/32	10	810-255	810-229
	1/2	12	810-256	810-230
	HEAVY DUTY BLACK POLYPROPYLENE			
	1/4	6	810-258	810-232
	5/16	8	810-259	810-B01-1A
	3/8	9	810-260	*810-B04-1C
	13/32	10	810-261	810-B05-1N
	1/2	12	810-262	810-B09-1M
	WHITE OCFIBER			
	1/4	6	810-263	810-237
	5/16	8	810-264	810-238
	3/8	9	810-265	810-B06-1T
	13/32	10	810-266	810-240
	1/2	12	810-267	810-B08-1W
	NYLON			
	1/8	3	810-268	*810-242
	5/32	4	810-269	810-B03-1Y
	3/16	5	810-270	810-244
	1/4	6	810-271	810-245
	5/16	8	810-272	810-B10-1W
	3/8	9	810-273	
	13/32	10	810-274	810-B07-1K
	1/2	12	810-275	810-249

ROPE COMPARISON CHART

ROPE WEIGHT AND STRENGTH SPECIFICATIONS FOR 3 STRAND STANDARD LAY (TWIST).

(Canadian Government Specifications.)


Nominal Size (Inches)		Weight Per 100 Ft. (Pounds)		Minimum Tensile Strength (Pounds)	
Diameter	Circumference	Nylon	Mono-filament Poly-propylene	Nylon	Mono-filament Poly-propylene
3/16"	5/8"	1.25	.80	1,100	720
1/4"	3/4"	1.90	1.37	1,700	1,120
5/16"	1"	3.08	1.80	2,700	1,490
3/8"	1-1/8"	4.00	2.70	3,500	2,120
7/16"	1-1/4"	5.00	3.80	4,300	2,820
1/2"	1-1/2"	7.00	4.90	5,950	3,650

Note: Safe Working Load is one seventh of the average tensile strength.

Synthetic rope is made from virgin fibres. It is much stronger than Manilla and Sisal. It is impervious to dampness, rot and mildew. Polypropylene in particular has the characteristics of lightness, smoothness, and will float.



C-913
Brass - Plain



C-1020
Steel - Zinc Plated

106-031
Steel - Zinc

CORD COUPLERS

SPAENAUR No.	Capacity Cord Size	Length	PKG QTY.
C-913	3/32" to 1/8"	1/2"	100
106-031	3/32" to 1/8"	1/2"	100
C-1020	1/8" to 3/16"	1"	100

2-PIECE TOOL SETS For Installation

T-247
T-247
T-248

Tool Sets have 3/8" arbor on top and bottom dies.
Will fit 876-830 Hand Press on page M26.