

**Electrical Wire Terminal Lugs / Splice Connectors**

Inch

**Cosses de conducteurs électriques / Connecteurs d'épissures**

Pouce



**Starter Lugs & Splices - Copper**

**Heavy Duty Power Lug - Tin Plated**




Increased wall thickness yields greater strength and conductivity. Tin plating offers corrosion resistance. Crimps with the same die setting as corresponding size battery terminal.



SPAENAUR No.	Cable Size	Stud Size	"B"	"L"	"W"	PKG QTY.
622-248	1/0	3/8"	.583"	2.00"	.84"	5
622-249	1/0	1/2"	.583"	2.00"	.84"	5
622-250	2/0	3/8"	.640"	2.25"	.91"	5
622-251	2/0	1/2"	.640"	2.25"	.91"	5
622-252	3/0	3/8"	.715"	2.25"	1.03"	5
622-253	3/0	1/2"	.715"	2.25"	1.03"	5
622-254	4/0	3/8"	.780"	2.40"	1.14"	5
622-255	4/0	1/2"	.780"	2.40"	1.14"	5

G

**Starter Lugs Light Duty Lugs (Unplated)**



SPAENAUR No.	Cable Size	Stud Size	"B"	"L"	"W"	PKG QTY.
622-256	6	1/4"	.232"	1.32"	.54"	10
622-257	6	3/8"	.232"	1.32"	.54"	10
622-258	6	1/2"	.232"	1.32"	.54"	10
622-259	4	1/4"	.286"	1.51"	.56"	10
622-260	4	5/16"	.286"	1.51"	.56"	10
622-261	4	3/8"	.286"	1.51"	.56"	10
622-262	2	1/4"	.336"	1.61"	.64"	10
622-263	2	3/8"	.336"	1.61"	.64"	10
622-264	1	1/4"	.360"	1.72"	.645"	10
622-265	1	3/8"	.360"	1.72"	.645"	10
622-266	1	1/2"	.360"	1.72"	.645"	10
622-267	1/0	3/8"	.407"	1.82"	.725"	10
622-268	1/0	1/2"	.407"	1.82"	.745"	10
622-269	2/0	3/8"	.461"	2.04"	.82"	10
622-270	2/0	1/2"	.461"	2.04"	.82"	10
622-271	3/0	3/8"	.511"	2.20"	.970"	10
622-272	3/0	1/2"	.511"	2.20"	.970"	10
622-273	4/0	3/8"	.559"	2.45"	1.09"	10
622-274	4/0	1/2"	.625"	2.45"	1.09"	10

**Cable Splices Tin Plated**



SPAENAUR No.	Cable Size	"B"	"D"	"L"	PKG QTY.
622-275	6	.232"	.312"	1.078"	5
622-276	4	.286"	.375"	1.219"	5
622-277	2	.336"	.437"	1.344"	5
622-278	1	.360"	.465"	1.344"	5
622-279	1/0	.407"	.515"	1.630"	5
622-280	2/0	.461"	.570"	1.797"	5
622-281	3/0	.511"	.630"	1.906"	5
622-282	4/0	.590"	.720"	2.000"	5