

Mattings / Glass Channel Packing / Rubber Sheets

Inch

Tapis / Ruban de fixation du verre / Feuilles de caoutchouc

Pouce



**BLACK RUBBER MATTING
NARROW GROOVE CORRUGATED**
1/8" Thick — 25 Yard Rolls

SPAENAUR No.	Width	Shipping Weight
7441-AN	24"	51 kg (112 lbs.)
7441-BN	36"	77 kg (170 lbs.)
7441-CN	48"	103 kg (227 lbs.)

PKG QTY. 25



**BLACK RUBBER MATTING
WIDE GROOVE CORRUGATED**
1/8" Thick — 25 Yard Rolls

SPAENAUR No.	Width	Shipping Weight
7441-AW	24"	61 kg (135 lbs.)
7441-BW	36"	92 kg (203 lbs.)
7441-CW	48"	122 kg (270 lbs.)

PKG QTY. 25

**Black PVC
ELECTRICAL
TAPE**



Adhesive backed. Replaces rubber and friction tape. Resists water, oil, acids and corrosive chemicals. Strong. For neat, lasting splices.

PKG QTY. 1

SPAENAUR No.	Tape Thickness	Size of Roll
TS-302	7.0 mil	3/4" x 66'
892-007	8.0 mil	3/4" x 66'



BLACK RUBBER (SBR) SHEET PACKING

Top Grade — 36" Wide — in 12 Yard Rolls

SPAENAUR No.	Width	Thick-ness	Construction	Shipping Weight
B-807A	36"	1/16"	Single cloth insert	38 kg (84 lbs.)

PKG QTY. 12 YARD ROLLS

All-Rubber SealStrip®

Special Strength - Tough cotton fibres make SealStrip® amazingly strong, but it trims easily without special tools. **Uniform Tackiness** - Clings to glass during application, holds tight when glass is set. Yet it peels off the roll easily, without tearing. **No Oil required** - Applies easily, without oil. For special applications, SealStrip® will absorb oil and swell sufficiently to ensure extra-strong grip. **Resists Age** - Thousands of applications prove that SealStrip® holds its physical characteristics, including tackiness throughout its life. Even moisture cannot affect the setting. **Won't Discolour Glass** - Laminated safety glass is safe from discolouration, because the specially compounded rubber used in SealStrip® will not bleed.

SPAENAUR No.	THICKNESS	WIDTH	FEET PER ROLL
B-168	1/32"	1-1/2"	100
B-169	3/64"	1-1/2"	100
834-A01-1C	3/32"	1-1/2"	100
834-001	1/16"	1-1/2"	100



PKG QTY. 1

**SBR OPEN AND CLOSED CELL
SPONGE RUBBER SHEETS**



SPAENAUR No.	THICKNESS	SIZE	STYLE
4537-R	1/4"	28" x 48"	Open Cell Soft Grade
RW-122	3/16"	23" x 44"	Closed Cell Soft Grade

PKG QTY. 1